

Annual Chemical Fume Hood Certification and Assessment

Industrial Hygiene and Safety (IHS) Office



rincipal Investigator:				Hood #: Hood Width:6'	
Department:			Location:	Date Last A	Assessed:
		_			
ace Velocit	_		ida de este a da a a		handlatan alama da da d
	-	-	-	_	hood into equal area grids of
			_		ity at the center of each grid.
Using the	ese measui	rements, an avera	ge face velocity w	as calculated.	
ſ	Face Veloci	ty in Feet Per Min	ute (fpm)		
0	,	0	0		
	'	U			
0)	0	0		
	·	O			
: <i>F</i>	Average Fa	ce Velocity =) Design Criteria for laboratorie
			requir	es an average face velocity o	f 80-120 fpm to pass.
Cross Draft \	-				
: F	otentially	interfering cross of	draft velocity shou	ıld not exceed 50 fpm, and ic	leally is less than 30 fpm.
isual Challe	enge Test I	<u>Results:</u>			
: S	Smoke gen	erated in the cher	nical fume hood a	ind around opening must be	completely contained.
		ty Assessment			
	1. Glass sash kept closed when not in use				6" from glass sash opening
2.	2. Loose paper towels or KimWipes not				ent works properly
left in hood					sily and does not drift
3.		baffle opening is	unblocked by		arm works properly
	items				quate (≥60 foot candles)
		residue is not on	hood surfaces		roperly wired and grounded
	5. Hood storage is minimal				eptable (≤63 dBA)
6	. Large Equ	uipment is raised	1" - 2" off base	14. Interior side p	anels secured
Commen	its:				
				ts USG Design Criteria for lab	
Fa				Design Criteria and is consider	
	<u>Do N</u>	<u>ot Use Hood</u> until	it is repaired and	rechecked for proper operat	ion by the IHS Office.
Date o	of Assessm	ent:	Assessme	nt Performed by:	